

| | | | | | |
|---|--|------------------------------|------------------------|------------------------------|------------|
| <div><div>NOA</div><div>PACKAGING</div></div> | TECHNICAL DATA SHEET | | | Document Code: | A.12.001 |
| | | | | Release Date: | 9.06.2022 |
| | | | | Revision Number: | 3 |
| | | | | Revision Date: | 11.11.2024 |
| | | | | Review Date: | 11.11.2024 |
| NP 500-K / 500 ML | | | | | |
| PRODUCT | | | | | |
| Product Code | | NP 500-K | | | |
| Product Description | | 500 Square Body + Lid | | | |
| Gross Volume (%±5) | | 540 | | | |
| Net Volume (%±5) | | 500 | | | |
| BODY DIMENSIONS | | | | | |
| Height (mm) (%±2) | | 90 | | | |
| Bottom Diameter (Ø) (%±2) | | 81 | | | |
| Outer Mouth Diameter (Ø) (%±2) | | 97 | | | |
| LID DIMENSIONS | | | | | |
| Height (mm) (%±2) | | 15 | | | |
| Outer Mouth Diameter (Ø) (%±2) | | 93 | | | |
| WEIGHT | | | | | |
| Body (±5) | | 23,83 | | | |
| Lid (±5) | | 7,89 | | | |
| Handle (±5) | | - | | | |
| Weight (±5) | | 31,72 | | | |
| RAW MATERIAL & COLOR | | | | | |
| Impact PP | | White Block Copolymer | | | |
| Random PP | | Transparent Random Copolymer | | | |
| Color | | On Request | | | |
| IML PRITING | | | | | |
| IML Printing Body | | Yes | | | |
| IML Printing Lid | | Yes | | | |
| PACKAGING UNITS | | | | | |
| Part Name | Box Size | Pieces in a Box | Box Quantity on Pallet | Number of Products on Pallet | |
| Body | 580x390x470 | 16 | 432 | 6912 | |
| Lid | 580x390x470 | 16 | 2280 | 36480 | |
| LOGISTICS INFORMATION | | | | | |
| Part Name | Body | | Lid | | |
| Quantity per Palet | 6912 | | 36480 | | |
| Quantity per Truck | 191762 | | 191762 | | |
| Quantity per 40'HC Container | 145274 | | 145274 | | |
| Free String | - | | - | | |
| EXPLANATIONS | | | | | |
| Hot Filling Conditions | The selected product has high temperature resistance and is suitable for hot filling. | | | | |
| | However, before purchasing the products, process trials should be carried out on the sample product. | | | | |
| Low Temperature Use | The production of products resistant to low temperatures requires special application. | | | | |
| | Products to be used at low temperatures should first be tested with samples. | | | | |
| Storage Conditions | Packaging should be stored in moisture-free, dry and closed environments away from direct sunlight. | | | | |
| Shelf life | It must be consumed within 2 years from the date of production. | | | | |
| Quality Information | Products are manufactured according to GFSI approved BRC, ISO 9001:2015 and ISO 22000 standards. | | | | |
| Packaging Change | Varies depending on desired quantities and pallet height. Noa Trade LTD. ŞTİ reserves the right to make changes. | | | | |

